#### Purdue University Purdue e-Pubs

LARS Symposia

Laboratory for Applications of Remote Sensing

1-1-1977

# Effects of Spatial Distortion on Image Registration Performance

Martin Svedlow

Clare D. McGillem

Paul E. Anuta

Follow this and additional works at: http://docs.lib.purdue.edu/lars\_symp

Svedlow, Martin; McGillem, Clare D.; and Anuta, Paul E., "Effects of Spatial Distortion on Image Registration Performance" (1977). *LARS Symposia*. Paper 176. http://docs.lib.purdue.edu/lars\_symp/176

This document has been made available through Purdue e-Pubs, a service of the Purdue University Libraries. Please contact epubs@purdue.edu for additional information.

Reprinted from

## Symposium on

## **Machine Processing of**

## **Remotely Sensed Data**

#### June 21 - 23, 1977

The Laboratory for Applications of Remote Sensing

Purdue University West Lafayette Indiana

IEEE Catalog No. 77CH1218-7 MPRSD

Copyright © 1977 IEEE The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org.

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

# EFFECTS OF SPATIAL DISTORTION ON IMAGE REGISTRATION PERFORMANCE

MARTIN SVEDLOW The Analytical Sciences Corporation Reading, Massachusetts 01867

CLARE D. McGILLEM AND PAUL E. ANUTA School of Electrical Engineering Purdue University West Lafayette, Indiana 47906

It is frequently desired to accurately register or overlay different images of the same scene. Under conditions in which the sensor-to-scene geometry is exactly the same for both images, the registration is accomplished by simply determining the relative translation between the images. However, in many instances there are variations in the sensor-to-scene geometry which cause the images to be spatially distorted relative to one another. This condition requires that a spatial warping be applied to one of the images in addition to determining the relative translation between the images in order to achieve registration.

For many situations in which the relative spatial distortion is small (e.g., temporally differing LANDSAT images), it is assumed that the spatial differences are negligible for small subimages. Registration is accomplished by overlaying corresponding subimages within each of the images via translation only and then applying a spatial warping to one of the images based upon the subimage registrations.

One of the primary parameters that must be determined in such a procedure is the subimage size to be used for registration. The analysis carried out presents a method by which the optimum image size may be chosen based upon a model of the spatial distortion and the premise that the registration processor is designed to overlay spatially congruent images. This is done by determining the effect of the relative spatial distortion upon the output signal-to-noise ratio of the registration processor. It is shown that for spatial distortions which increase with image size (e.g., rotation, scale difference), there is an optimal image size which maximizes the output signal-to-noise ratio. The analysis is also applied to a model of spatial distortions between temporally differing LANDSAT images.

1977 Machine Processing of Remotely Sensed Data Symposium