

1-1-1977

# Feature Space Transformation for Improved Interpretability of Color Images

H. K. Ramapriyan

Follow this and additional works at: [http://docs.lib.purdue.edu/lars\\_symp](http://docs.lib.purdue.edu/lars_symp)

---

Ramapriyan, H. K., "Feature Space Transformation for Improved Interpretability of Color Images" (1977). *LARS Symposia*. Paper 183.  
[http://docs.lib.purdue.edu/lars\\_symp/183](http://docs.lib.purdue.edu/lars_symp/183)

This document has been made available through Purdue e-Pubs, a service of the Purdue University Libraries. Please contact [epubs@purdue.edu](mailto:epubs@purdue.edu) for additional information.

Reprinted from

**Symposium on  
Machine Processing of  
Remotely Sensed Data**

**June 21 - 23, 1977**

The Laboratory for Applications of  
Remote Sensing

Purdue University  
West Lafayette  
Indiana

IEEE Catalog No.  
77CH1218-7 MPRSD

Copyright © 1977 IEEE  
The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to [pubs-permissions@ieee.org](mailto:pubs-permissions@ieee.org).

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

# FEATURE SPACE TRANSFORMATION FOR IMPROVED INTERPRETABILITY OF COLOR IMAGES

H. K. RAMAPRIYAN

Computer Sciences Corporation, Systems Sciences Division, 8728 Colesville Road, Silver Springs, Maryland 20910

Several mappings of the feature space are in vogue for generating user-oriented products from remotely sensed data. A classification map with different colors assigned to each of the say,  $n$ , classes of interest may be looked upon as a result of a nonlinear transformation of the feature space into  $n$  points in the "color" space. This is a useful mapping in areas such as land use or water resources studies. However, in areas such as interpretation of geological images, the analyst is generally interested in preserving the texture of the image and analyzing the information manually. Therefore, other methods of enhancing the interpretability of the image such as principal components and canonical analyses are employed.

The principal components analysis provides a linear mapping such that the "information" along each of the transformed axes is maximized. Canonical analysis obtains a linear transformation based on maximizing the separation among given categories along the coordinate axes. These transformations, while useful in reducing dimensionality, tend to produce different tones in the same color, rather than different colors, for the most separable classes.

The purpose of this paper is to develop a linear transformation which assigns data from different chosen categories, modeled parametrically or nonparametrically, into specified colors. The approach taken is to specify that the given categories be mapped into given vectors in the "color" space and minimize the mean squared error between the transformed data and the given vectors. When the specific colors say  $C_1, C_2, C_3, C_4$ , assigned to given classes say  $P_1, P_2, P_3, P_4$ , are irrelevant, the mean squared error can be reduced by considering all combinations of assignments such as  $[(P_1 \rightarrow C_1), (P_2 \rightarrow C_2), (P_3 \rightarrow C_3), (P_4 \rightarrow C_4)]$ ,  $[(P_1 \rightarrow C_2), (P_2 \rightarrow C_1), (P_3 \rightarrow C_3), (P_4 \rightarrow C_4)]$  and so on.

Experimental results are shown to

illustrate the transformation.

---

This work was performed under Contract No. NAS5-11999 from NASA, Goddard Space Flight Center, Greenbelt, Maryland