

1-1-1977

A Land Use Change Monitoring System Based on LANDSAT

Gary L. Angelici

Nevin A. Bryant

Follow this and additional works at: http://docs.lib.purdue.edu/lars_symp

Angelici, Gary L. and Bryant, Nevin A., "A Land Use Change Monitoring System Based on LANDSAT" (1977). *LARS Symposia*. Paper 232.

http://docs.lib.purdue.edu/lars_symp/232

This document has been made available through Purdue e-Pubs, a service of the Purdue University Libraries. Please contact epubs@purdue.edu for additional information.

Reprinted from

**Symposium on
Machine Processing of
Remotely Sensed Data**

June 21 - 23, 1977

The Laboratory for Applications of
Remote Sensing

Purdue University
West Lafayette
Indiana

IEEE Catalog No.
77CH1218-7 MPRSD

Copyright © 1977 IEEE
The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org.

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

A LAND USE CHANGE MONITORING SYSTEM BASED ON LANDSAT

GARY L. ANGELICI AND NEVIN A BRYANT
Jet Propulsion Laboratory, Pasadena,
California, 91103

A procedure for economically determining statistics on acreages of change in the use of land between two dates has been developed to support a Department of Housing and Urban Development program on neighborhood change modelling. The application of image processing techniques to LANDSAT imagery in four stages (registration, differencing, classification, and tabulation) provides one of the basic data sets needed to model future land use in one of six "typical" urban areas.

After appropriate LANDSAT imagery for two desired dates is obtained, date-to-date registration of the study area is performed. Once the two images are adequately registered, the procedures of determining the geographic areas of change are initiated. The ratio of two raw bands for the early date is computed and then subtracted from the same ratio for the late date. This difference is allowed to conform to a gaussian distribution, and those pixels whose values lie beyond two standard deviations from the mean are designated as areas of change.

The first step in the creation of a late date classification map is to extract and classify only those areas that show change. Then the early date classified data for unchanged areas is digitally summed with the late date classified data in changed areas.

Using polygon overlay routines individually for both the early and late date classifications and then combining the results, a tabulation revealing general land use changes (e.g., the number of acres of residential in the early date versus the number in the late date) can be generated. To determine the manner of the change (e.g., the number of acres changed from rural to urban), the land use classes are first aggregated into rural/urban dicotomies and then a routine which permits comparison of individual pixel values is executed. Finally, a tabulation can display the manner of the land use change aggregated by the administrative district desired (e.g., census tracts).