

1-1-1979

Three-Dimensional Object Representation for Exploitation of Remotely Sensed Images

Michael Shantz

George Huang

Follow this and additional works at: http://docs.lib.purdue.edu/lars_symp

Shantz, Michael and Huang, George, "Three-Dimensional Object Representation for Exploitation of Remotely Sensed Images" (1979). *LARS Symposia*. Paper 249.
http://docs.lib.purdue.edu/lars_symp/249

This document has been made available through Purdue e-Pubs, a service of the Purdue University Libraries. Please contact epubs@purdue.edu for additional information.

Reprinted from

**Symposium on
Machine Processing of
Remotely Sensed Data**

June 27 - 29, 1979

The Laboratory for Applications of
Remote Sensing

Purdue University
West Lafayette
Indiana 47907 USA

IEEE Catalog No.
79CH1430-8 MPRSD

Copyright © 1979 IEEE
The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org.

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

THREE-DIMENSIONAL OBJECT REPRESENTATION FOR EXPLOITATION OF REMOTELY SENSED IMAGES

DR. MICHAEL SHANTZ AND DR. GEORGE HUANG

Ford Aerospace & Communications Corp.

The value of digital 3-D object representation as an aid to exploit remotely sensed images has been demonstrated. Experience has shown that knowledge about what is being viewed is required to accomplish non-trivial object recognition tasks when such an aid is used. Previous approaches representing knowledge as constraints in a relaxation scheme or as templates for pattern matching, lack flexibility and realism. This paper presents recent research results on a shaded surface computer graphics approach that uses a knowledge base consisting of a library of three-dimensional objects represented as surfaces and skeletons. Objects include pieces of terrain, vehicles and buildings. The surfaces for these objects are generated by mapping surfaces onto topological contours or onto a series of cross sectional object outlines. For branching contours (n contours in section i connecting to m contours in section $i+1$), the surfaces are mapped by first concatenating the section i contours into a single large contour, similarly concatenating the section $i+1$ contours, then performing the one to one mapping. Capping off single arbitrarily shaped contours is done by computing the medial axis transform of the contours, constructing the medial axis contour and then mapping a surface from the contour to the medial axis contour. The skeleton of a general three-dimensional closed polygonal surface may be obtained through use of a three-dimensional extension of the medial axis transform. This research has resulted in a mapping algorithm that provides a more general method for obtaining surface descriptions of non-analytic contour defined objects suitable for placement in a scene and for shaded surface rendition. Furthermore, depth profiles of the scene may be generated, which are useful for comparisons with actual depth information.