1-1-2007

Safe Excavation

Purdue ECT Team
Purdue University, ectinfo@ecn.purdue.edu

DOI: 10.5703/1288284315781

Follow this and additional works at: <https://docs.lib.purdue.edu/ectfs>

Part of the [Civil Engineering Commons](#), and the [Construction Engineering and Management Commons](#)

Recommended Citation

ECT Team, Purdue, "Safe Excavation" (2007). *ECT Fact Sheets*. Paper 72.
<http://dx.doi.org/10.5703/1288284315781>

This document has been made available through Purdue e-Pubs, a service of the Purdue University Libraries.
Please contact epubs@purdue.edu for additional information.

SAFE EXCAVATION

THE NEED

Excavating with a backhoe or similar equipment has the potential risk of hitting an underground utility which could cause serious injuries and expensive damages. Contractors usually rely on utility companies or other professional services to mark the area where cables or pipes are buried. But without being able to know the depth and exact position of the line. The Occupational Safety and Health Administration - OSHA - estimated that the fatality rate was at 50.8 deaths per 100,000 workers per year from 1984 to 1988. The National Institute of Occupational Safety and Health estimated that at least 127 persons were killed as a result of all excavation-related accidents (Huang et al. 1996).

THE TECHNOLOGY

An electronic device that provides a real-time warning of the utility lines immediately ahead of the digging tool and provides an easily interpreted, real-time computer readout of the depth, location, and size buried metallic objects. Developed by Dr. Leonhard E. Bernold, it consists of an active metal detector search coil; a signal processing (control) unit; and a PC computer equipped with an analog-to-digital converter interface. The active metal detector generates a magnetic field. Its impact on any metal object in its detection range is picked up by the control unit. The data is converted from analog to digital at a high sampling rate and transmitted to the computer. The computer receives real-time data about magnetic changes in the detector vicinity, graphs it on the screen, sounds a signal, and stores it in a file for future analysis.

THE BENEFITS

The device helps in the detection and location of hidden underground cables, gas pipes, toxic waste drums and even bombs. It is a portable system that can be attached to backhoes, trenchers and other digging equipment.

STATUS

The system is ready for implementation but the designer is looking for investors and a production contract. An actual job site application of the system has not yet occurred.

An enhanced device is being developed that can detect plastic-coated utility cables and fiber-optic telephone lines.

BARRIERS

The cost of the system is the current major barrier because of the lack of a production contract. The device will not detect plastic pipes or objects that do not have a metallic component. The detection depth or range of the system is limited by the capacity of the active metal detector.

POINTS OF CONTACT

Leonhard Bernold, North Carolina State University

Tel: (919) 515-3677

REFERENCES

1. Huang, X., Bernd, D., and Bernold, L.E. "Equipment Mounted Buried Utility Detection System"
2. Huang, X., Bernd, D., and Bernold, L.E. 'Innovative Technology Development for Safe Excavation' Journal of Construction Engineering and Management, Vol. 122, No. 1, March, 1996.
3. 'New N.C. State Device Uncovers Hidden Dangers Underground' North Carolina State University News Release, August 16, 1995.

REVIEWERS

Peer reviewed as an emerging construction technology

DISCLAIMER

Purdue University does not endorse this technology or represents that the information presented can be relied upon without further investigation.

PUBLISHER

Emerging Construction Technologies, Division of Construction Engineering and Management, Purdue University, West Lafayette, Indiana