

8th International Conference on Physical and Numerical Simulation of Materials Processing (ICPNS)

14–17 October 2016

Seattle, Washington | Hosted by Purdue University

## SESSION 5: IRON AND STEEL, HARBOR HALL

Co-Chairs: Jer-Ren Yang, National Taiwan University; Zhaoxia Qu, Welding and Corrosion Protection Technology Department Research Institute; Josip Brnic, University of Rijeka; Hiromi Miura, Nippon Steel & Sumitomo Metal Corp

SATURDAY, OCTOBER 15, 2016

---

# Research on the impact of geometric parameter on the cross-section precision

Yang Hong Liang; Xing Zhong Wen; Hao Zhao, Harbin Institute of Technology

## ABSTRACT

Tube with rectangular section produces cross-section distortion easily in the process of bending, affecting the forming precision. Taking the rotary draw bending of high-strength steel BR1500HS tube shaped rectangular section for the study object, the article puts forward the description method of cross-section distortion, and tests the rule that cross-sectional position, wall thickness, bend radius, and other geometric parameters influence on cross-section precision after rotary draw bending through experiments. The finite element model of high-strength steel tube with rectangular cross-section about rotary draw bending is established based on ABAQUS software platform, the experiment and simulation results are compared. The results showed that after cross-section distortion, it is approximately trapezoidal, and the maximum of distortion exists in 45–60°C of rotary draw bending direction, the absolute and relative distortion values decrease as the thickness or bending radius increases. The simulation and experimental results agree well. So, the results provide a reference about selecting geometric parameters on high-strength steel tube with rectangular section in rotary draw bending.

**KEYWORDS:** tubes with rectangular section, high-strength steel, rotary draw bending, cross-section precision