

1-1-1980

Quantitative Use of Ancillary Data in Pixel Labeling

J. A. Richards

D. A. Landgrebe

P. H. Swain

Follow this and additional works at: http://docs.lib.purdue.edu/lars_symp

Richards, J. A.; Landgrebe, D. A.; and Swain, P. H., "Quantitative Use of Ancillary Data in Pixel Labeling" (1980). *LARS Symposia*. Paper 382.

http://docs.lib.purdue.edu/lars_symp/382

This document has been made available through Purdue e-Pubs, a service of the Purdue University Libraries. Please contact epubs@purdue.edu for additional information.

Reprinted from

**Symposium on
Machine Processing of
Remotely Sensed Data
and
Soil Information Systems
and
Remote Sensing and Soil Survey**

June 3-6, 1980

Proceedings

The Laboratory for Applications of Remote Sensing

Purdue University
West Lafayette
Indiana 47907 USA

IEEE Catalog No.
80CH1533-9 MPRSD

Copyright © 1980 IEEE
The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org.

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

QUANTITATIVE USE OF ANCILLARY DATA IN PIXEL LABELING

J. A. RICHARDS

University of New South Wales, Australia

D. A. LANDGREBE AND P. H. SWAIN

Purdue University/LARS

Ancillary data such as elevation, slope, rainfall, crop planting date, etc., have been recognized for some time as containing useful information for improving data analysis accuracy. However, means for incorporating data of this sort into the analysis process have seen only limited development. For example, ancillary data have been used in a more or less subjective manner in the class definition and training process and in partitioning class sets into mutually exclusive subsets. The purpose of the work reported here is to find more objective and quantitative means for using this ancillary information.

Relaxation techniques are a class of iterative procedures under study in the field of picture processing wherein they show promise for reducing ambiguity in scene labeling by developing spatial context.

In this paper initial results are presented to show how relaxation techniques can be adapted to the pixel labeling problem to utilize ancillary data in a quantitative and objective fashion. The technique is highlighted by a forestry example in which elevation is used as ancillary data to improve the accuracy of an existing classification of cover types.