*EFFECT OF RATE OF STRAIN ON
THE STRENGTH OF COMPACTED SOIL*

*DEC., 1958
NO. 31*

*Joint
Highway
Research
Project*

by

D. HAMPTON
E. J. YODER

PURDUE UNIVERSITY
LAFAYETTE INDIANA

Technical Paper

TO: K. B. Woods, Director
Joint Highway Research Project

FROM: H. L. Michael, Assistant Director
Joint Highway Research Project

December 18, 1958

File: 6-8-2
Project: C-36-14B

Attached is a technical paper entitled, "Effect of Rate of Strain on the Strength of Compacted Soil." The paper has been prepared by Mr. Delon Hampton and Prof. E. J. Yoder of our staff. The paper was prepared from research conducted by Mr. Hampton under the direction of Professor Yoder and was also used by Mr. Hampton for his research for the M.S.C.E. degree. The paper will be presented at the annual meeting of the Highway Research Board in Washington, D. C. in January 1959.

The paper is presented for the record.

Respectfully submitted,

H. L. Michael, Secretary

HLM:acc

Attachment

cc: J. R. Cooper
W. L. Dolch
W. H. Goetz
J. T. Hallett
F. F. Havey
G. A. Hawkins (M. B. Scott)
G. A. Leonards
J. F. McLaughlin
R. D. Miles
R. E. Mills
B. H. Petty
C. E. Vogelgesang
J. L. Waling
J. E. Wilson
E. J. Yoder

Technical Paper

EFFECT OF RATE OF STRAIN ON THE
STRENGTH OF COMPACTED SOIL

by

Delon Hampton, Graduate Assistant
and
E. J. Yoder, Research Engineer

Joint Highway Research Project
Project No: C-36-14B
File No: 6-8-2

Purdue University
Lafayette, Indiana
December 18, 1958

Prepared for Presentation at the
38th Annual Meeting of the Highway Research Board
January 5-9, 1959, Washington, D. C.

Not for Publication

(Subject to Change Before Publication)

Digitized by the Internet Archive
in 2011 with funding from

LYRASIS members and Sloan Foundation; Indiana Department of Transportation

Synopsis

This paper reports the results of a laboratory investigation of the effects of rate of strain on the strength of remolded soil. Two soils were selected for purposes of this study: (a) a clay derived from limestone and pedologically classified as Frederick, and (b) a glacial silty clay, pedologically classified as Crosby, "B" horizon. These soils were selected primarily on the basis of their difference in plasticity.

Rate of strain was considered the most important variable and it was studied from 0.55 in./min. to 1780 in./min. The factors of moisture content and dry density were also of prime importance. Consequently, three compactive efforts were used and specimens were molded and tested on both sides of the optimum moisture content of each compactive effort.

The unconfined compressive strength test was used as the strength criterion, and the effect of the aforementioned variables upon the ultimate strength and modulus of deformation of the samples, as determined by this test, are reported.

INTRODUCTION

The fact that the compressive strength is a function of the time required to reach the failure load has long been recognized. However, this area of soil mechanics has not been extensively explored and much work remains to be done, in order that the effects of this phenomenon can be properly evaluated. The specific areas where this information would be of the greatest benefit are as follows:

- (a) stability of slopes subjected to earthquakes and other forms of transient loading,
- (b) transmission of forces from explosions through soils,
- (c) design of highway pavements, and
- (d) design of airfield pavements.

Stability of Slopes

In areas where there is a possibility of earthquakes, it is of the utmost importance to investigate the stability of slopes, both natural and man-made, under transient conditions. Such an investigation is especially necessary when failure of the slope in question would be disastrous. Earthquake shocks induced in the earth represent transient loading conditions and critical slopes should be designed and analyzed on this basis.

Transmission of Forces from Explosions

The transmission of forces from explosions through soil, due to the short time of loading, is another example of where structures subject to such forces should be designed and analyzed on the basis of transient loading tests. Such a rigorous study would be valid only for critical military installations.

Design of Highway Pavements

It is generally recognized that the stress-strain characteristics of pavements are a function of the rate of strain. This can be readily seen by observing the condition of pavements at critical sections along a given route.

From such studies, it has been found that road intersections, uphill grades and other sections where traffic is required to move slowly, or to stop, show distress much more rapidly than their counterparts i.e. open road, free of stops, and downhill grades. This is believed to be caused, in part, by the difference in speed of travel over the aforementioned sections. As a result, there is much need of a comprehensive study on the effect of rate of strain on the behavior of soils.

Design of Airfield Pavements

Because of the high speed at which airplanes travel over runways, the latter are subjected to transient loading conditions which are vastly different from the relatively static conditions to which the aprons, taxiways, and ends of runways are subjected. Hence, it is desirable to evaluate the stress-strain characteristics of the paving materials under both transient and static loading. Such a procedure would lead to the most economical as well as the best design.

PURPOSE AND SCOPE

The previous discussion points out that the effect of rate of strain on the strength of soil is important. Consequently, the primary purpose of the research reported herein was to investigate the strength properties of a clay and silty clay under conditions of transient loading. Specifically the aim was to ascertain the relationship between rate of strain and unconfined compressive strength at various moisture contents and densities. Also, it was hoped to relate the aforementioned variables to the modulus of deformation.

Rate of strain was considered the most important variable, and it was studied from 0.55 in./min. to 1730 in./min. Soil texture was a second variable and two fine-grained soils of significantly different characteristics were chosen - a silty clay and a clay. All soils are native to Indiana.

The factors of moisture content and dry density were also of prime importance. Three compactive efforts were used and specimens were molded and tested on both sides of the optimum moisture content (O.M.C.), of each compactive effort.

DEFINITIONS

It is assumed that the reader is familiar with terms pertaining to conventional strength tests on soils. However, before proceeding further he should familiarize himself with the following terms:

- (a) A Slow Transient Compression Test is one in which the rate of strain lies within the range of 0.45 in./min. to 0.6 in./min.
- (b) A Medium Transient Compression Test is one in which the rate of strain lies between 11.0 in./min. and 15.5 in./min.
- (c) A Fast Transient Compression Test is one in which the rate of strain is greater than 250 in./min.
- (d) Time of Loading is defined as the difference in time between the start of a loading test and the time at which the maximum compressive stress is reached.
- (e) Compressive Stress is the axial load per unit of cross sectional area of a test specimen. In computing the compressive stress, a correction was applied to the area assuming that no volume change took place, i.e. change in area assumed proportional to the change in height.
- (f) Modulus of Deformation is a secant modulus defined as the slope of a line from the origin through the point on the stress vs. strain curve at which the stress is one-half of the compressive strength. Or, if the initial part of the stress vs. strain curve is straight, it is the slope of this portion of the curve.
- (g) Rate of Strain is defined as the deformation at failure divided by the time required to reach failure.
- (h) Strength Ratio, S_R , is defined as the ratio of the strength, for a given rate of strain, to that for a slow transient test at the same moisture content and for the same compressive effort.

(i) Modulus of Deformation Ratio, M_D , is defined as the ratio of the modulus of deformation for a given rate of strain to that for a slow transient test at the same moisture content and for the same compactive effort.

(j) Strength, in this report will always apply to the axial load required to produce failure in an unconfined compression test.

It should be noted that the above definitions may be at variance with those by other investigators, but were adopted for this study because they give the best representation of the data.

REVIEW OF LITERATURE

The effect of time of loading on the strength and modulus of elasticity of metal and concrete has been extensively investigated. Also, a considerable amount of work has been done on rock and wood, but little on soil.

The standard methods of measuring the time effect, in previous investigations, was either by the time of loading, the rate of loading, or the rate of strain. In general, the method utilized was determined by the characteristics of the testing machines, i.e. with the equipment available which of the aforementioned methods of measurement can be used most accurately and efficiently. Nevertheless, whenever the time-stress-strain relationships are known, any one of the above ways of measuring the time effect may be converted to either of the other two.

Soil

In connection with the design of the Panama Canal, several triaxial compression tests were made to determine the effect of time of loading on the compressive strength of Gatun black muck (14)*. In one test, with a time of loading of approximately 90 seconds, the compressive strength was about 40 per cent greater than in 4 other tests in which failure was obtained in about 1 hour.

A series of triaxial compression tests, on remoulded-consolidated Boston blue clay, was reported by Taylor. The rate of strain ranged between 1 and 0.0005 per cent per minute and the compressive strength for the fastest test was approximately 20 per cent greater than that for the slowest test (1).

* Numbers in parentheses refer to references in the bibliography.

Casagrande and Shannon (1) found that the modulus of deformation of clays for fast transient tests was approximately twice as great (for both unconfined and consolidated quick tests) as that for slow tests. Also, the modulus of deformation of Manchester sand increased slightly with decreasing time of loading i. e. the average value for static tests is about 300 kg. per sq. cm. and for fast transient tests about 400 kg. per sq. cm.

Furthermore, for all tests on clays the transient compressive strength was greater than the static compressive strength. The fast transient compressive strength, taken at a time of loading of 0.02 seconds, ranges between 1.5 and 2.5 times greater than the 10 minute static compressive strength. The above holds true regardless of whether the clay is undisturbed or remolded.

Tests on the Manchester sand indicate that the transient compressive strength of sand in a fast transient compression test was only about 15 per cent greater than the static compressive strength.

Investigations by Seed and Lundgren (15), on the effect of transient loading on the strength of saturated sands supports the above. It was found that the strength of dense specimens in rapid transient tests was 15 to 20 per cent greater than the strengths of similar specimens in static or slow transient tests.

Whitman (23), also, found that the strength of both undisturbed and disturbed soil specimens was significantly increased by transient loading. This work was done over a wide range of cohesive soils and three sands -- the latter ranging from uniform Ottawa sand to well-graded sands.

On the basis of the data collected Whitman concluded that the effect of rate of strain on cohesive soils should be evaluated from

triaxial tests with confining pressures adequate to prevent splitting or shear plane development prior to the occurrence of the peak load. Considering dry sand and moist sand, it was found that increasing the rate of strain did not produce a significant change in the strength of the material. However, the converse was true for saturated sand and Whitman attributed this to differences in pore water pressures in the slow and rapid tests.

DESCRIPTION OF MATERIALS

Two soils were selected for purposes of this study: (a) a red-colored clay derived from limestone, and (b) a brown glacial silty clay, pedologically classified as Crosby, "E" horizon; both soils are native to Indiana. These soils were selected primarily on the basis of their difference in plasticity (Table 1).

Both soils were air dried, pulverized, and passed through a Number 40 U. S. Standard Sieve. It is recognized that a soil containing clay is irreversibly altered by drying, particularly if the drying is allowed to reach the shrinkage limit. Thus, the laboratory behavior of these soils is peculiar to their processed condition and may differ significantly from the in situ behavior.

TABLE 1
SUMMARY OF ATTERBERG LIMITS

Soil	LL	PL	PI	Classification	
				HRB	Unified
Silty Clay	35.4	19.3	15.9	A-6	CL
Clay	72.0	28.1	43.9	A-7-6	CH

Moisture-Density Relationships

The only relationships studied were those for kneading type compaction with three compactive efforts being used. There is no recognized standard procedure for the equipment used, for the Harvard Miniature Compaction apparatus; however, the compaction procedure recommended in reference (22) was followed.

It was hoped to obtain densities which approximated the Standard AASHTO and Modified AASHTO compaction tests as well as a density intermediate between the two. The moisture vs. density curves are shown in Figures 2 and 3. Also as a comparison between the dynamic and the kneading compaction characteristics of these soils Table 2 is presented. The data presented, in Table 2, on kneading compaction represents the average values obtained from the three moisture density curves in Figures 2 and 3.

The Harvard Compaction Apparatus produces specimens 2.816 inches long and 1 5/16 inches in diameter. The volume of the compaction cylinder is 1/454th of a cubic foot which means that the weight of a compacted specimen in grams is numerically equal to its unit weight in pounds per cubic foot. The samples so obtained were used to establish the moisture density curves as well as for strength tests.

The compactive efforts used were 10 layers at 50 blows per layer, which approximates the Modified AASHTO, and three layers at 25 blows per layer which gives dry densities comparable to the Standard AASHTO test. The third compactive effort varied depending on the soil being tested. The latter was necessary in order to obtain significant differences in the dry densities obtained from the three compactive efforts. For the

TABLE 2

COMPARISON OF KNEADING AND DYNAMIC COMPACTION*

Soil	Compactive Effort	Max. (pcf)	D.M.C. (%)
Silty-Clay	Standard AASHO	107.5	19.2
	Kneading Compactor (3 layers at 25 blows)	109.5	18.3
	Modified AASHO	119.3	13.7
	Kneading Compactor (10 layers at 50 blows)	117.0	11.8
Clay	Standard AASHO	91.7	27.6
	Kneading Compactor (3 layers at 25 blows)	94.8	26.0
	Modified AASHO	106.7	19.5
	Kneading Compactor (10 layers at 50 blows)	102.5	22.7

*Data for dynamic compaction obtained from Reference (15).

Croaky "B" soil the intermediate compactive effort was ten layers at 25 blows per layer while that for the Frederick limestone soil was ten layers at ten blows per layer.

Unconfined Compressive Tests

The unconfined compressive strength tests were run on either a hydraulic loading apparatus or the impact loading apparatus depending upon the rate of strain desired. The dynamic loading apparatus consists of a ten pound weight dropped 39 inches upon a piston which applied the load to the specimen. In order to prevent damage to the loading frame and measuring instruments, and to slow down the rate of loading, a spring was inserted atop the loading piston. Another advantage was that the elasticity of the spring caused the weight to bounce, whereupon it was caught before it could again come in contact with the piston.

Collection of Data and Instrumentation

Low voltage differential transformers were employed to measure the load as well as the deformation during the compression process. In this type gage the output voltage of the secondary coils which are excited by a primary coil is proportional to the displacement of a magnetic core within these coils.

A schematic diagram of the load and deformation apparatus is shown in Figure 1. It can be seen that as the proving ring deforms the position of the core moves relative to the coils. Also, as the arm of the strain gage deflects the core contained therein moves relative to its primary and secondary coils. These movements produce changes in the output voltage, of these two instruments, which can be measured. A Model 655 Audio Oscillator operating at a frequency of 3000 cps. was used to energize the transformers.

FIG. 1 SCHEMATIC DIAGRAM OF TEST SET-UP

To record the changes in stress and strain during the progress of the test a Dumont Cathode-Ray Oscilloscope was used. In this study, the deflection of the oscilloscope trace was made proportional to the output of the differential transformers.

RESULTS

Strength

In both the clay and the silty clay, the strength vs. moisture content curves all exhibited a "peaked" shape, as indicated in Figures 2 and 3. Theoretically the strength should continue to rise as the moisture content decreased. However, there was a tendency for a reduction in this "peaked" condition as the rate of strain increased.

There are two possible reasons for the aforementioned; (a) the condition is the result of the inherent characteristics of the test i.e. at low moisture contents the specimens fail by crumbling rather than shear, due to a lack of lateral confinement, or (b) the condition is a result of the molding process i.e. kneading type compaction imparts this characteristic to the soil.

At the lower moisture contents tested, 9-10 per cent for the silty clay and 14-15 per cent for the clay, the specimens were brittle and would crumble around the edges if not handled carefully. There is great possibility that this tendency existed at higher moisture contents but was just more difficult to detect.

In all cases the maximum strength, as indicated from these tests, occurred at a moisture content less than optimum (Figures 2 and 3). Exactly how much seemed to depend upon the rate of strain and the compactive effort i.e. as the compactive effort decreased there was a tendency for the difference between O.M.C. and the moisture content at which maximum strength occurred to increase. The maximum difference between the latter two was approximately 4 per cent in the silty clay and 5 per cent in the clay.

Once the moisture content at which the optimum strength was obtained was passed, the change in strength for a given change in

FIG. 2 MOISTURE CONTENT VS. DRY DENSITY, UNCONFINED COMPRESSIVE STRENGTH, AND MODULUS OF DEFORMATION
SILTY CLAY

FIG. 3 MOISTURE CONTENT VS. DRY DENSITY, UNCONFINED COMPRESSIVE STRENGTH, AND MODULUS OF DEFORMATION — CLAY

moisture content increased significantly (Figures 2 and 3). It appears that the greater the rate of strain the steeper this portion of the curve becomes.

The foregoing is true for both the silty clay and clay. However, in the clay, the rate of increase of strength for a given increase in moisture content on the dry side of optimum strength was equal and in some instances greater than the rate of decrease which occurred on the wet side. Whether or not this is significant depends on the validity of the tests conducted on the dry side i.e. whether or not the specimens were failing principally by crumbling or by shear.

Silty Clay

It was found that, for a given compactive effort and moisture content, increasing the rate of strain produced a measurable increase in the strength of the soils (Figures 4 and 6). In the case of the silty clay, for the lowest compactive effort, an increase of over 100 per cent in the unconfined compressive strength was obtained by increasing the rate of strain from 0.55 in./min. to 1768 in./min., regardless of the moisture content of the sample (Table 3). For the highest compactive effort the increase in strength for the same change in rate of strain ranged between 52 and 87 per cent while for the intermediate compactive effort the range was from 20 to 89 per cent.

As regards the change in strength of the medium transient test with respect to the slow transient test, for a given density and compactive effort, the increase in strength was much less (Table 3). Considering the lowest compactive effort the increase in strength ranged from 12 to 32 per cent, for the intermediate compactive effort the change ranged from -17 to 40 per cent, and for the highest compactive effort the change in strength was from +10 to +51 per cent.

FIG. 4 RATE OF STRAIN VS. UNCONFINED COMPRESSIVE STRENGTH
 SILTY CLAY

TABLE 3

SUMMARY OF RESULTS OF STRENGTH TESTS-SILTY CLAY

RATE STRAIN	COMPACTIVE EFFORT					
	3 Layers/25 Blows		10 Layers/25 Blows		10 Layers/50 Blows	
	MOISTURE CONTENT = 10%					
	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio
0.55 "/min.	43	1.00	81	1.00	85	1.00
14.5 "/min.	48	1.12	110	1.36	128	1.51
1768 "/min.	109	2.54	153	1.89	159	1.87
	MOISTURE CONTENT = 12%					
	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio
0.55 "/min.	46	1.00	83	1.00	103	1.00
14.5 "/min.	61	1.33	116	1.40	130	1.26
1768 "/min.	119	2.59	146	1.76	156	1.52
	MOISTURE CONTENT = 14%					
	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio
0.55 "/min.	43	1.00	77	1.00	91	1.00
14.5 "/min.	57	1.32	96	1.25	110	1.21
1768 "/min.	95	2.21	127	1.65	140	1.54
	MOISTURE CONTENT = 16%					
	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio
0.55 "/min.	34	1.00	57	1.00	51	1.00
14.5 "/min.	43	1.26	56	0.98	62	1.22
1768 "/min.	71	2.09	88	1.54	93	1.82
	MOISTURE CONTENT = 17%					
	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio
0.55 "/min.	28	1.00	46	1.00	38	1.00
14.5 "/min.	35	1.25	38	0.83	42	1.10
1768 "/min.	57	2.04	55	1.20	58	1.53

There appears, on the basis of the data collected, to be a general trend toward a decrease in the effect of rate of strain as the moisture content increases, for a given compactive effort (Figure 4 and Table 3). This, in all probability, is due to the greater effect of pore water pressures which would tend to decrease the strength of the sample. This could also be the reason why the strength ratio values tend to decrease as the compactive effort increases.

From the foregoing discussion, it can be seen that the effect of rate of strain is more significant in increasing the strength of material at low densities. In comparing the fast and slow transient tests, over 100 per cent increase in strength was obtained for the lowest compactive effort. Considering the same range for the other two compactive efforts the maximum increase was 89 per cent, and for the majority of cases it was much less.

Furthermore, as the compactive effort increased the effect of an increase in moisture, on the strength, increased for a given compactive effort (Figure 4). As aforementioned, this is due to an increase in pore pressure brought about by a reduction in void ratio due to increased compaction.

From Figure 5, which is a plot of unconfined compressive strength vs. dry density, at constant moisture content, it can be qualitatively stated that the effect of increased density decreases as rate of strain increases. For example, it can be noted that the slopes of the curves for rate of strain equal to 1768 inches per minute are less than those for either 0.55 or 14.5 inches per minute. Also, moisture content did not effect the slopes appreciably.

FIG. 5 DRY DENSITY VS. UNCONFINED COMPRESSIVE STRENGTH-SILTY CLAY

Clay

For the clay, it was also found that for a given compactive effort and moisture content, increasing the rate of strain produced a measurable increase in the strength of the soil (Figure 6). As with the silty clay, the strength ratio, for all moisture contents, was greatest for the lowest compactive effort (Table 4). Also, from Figure 6 it can be seen that moisture content has less effect on the strength, at a given rate of strain, the lower the compactive effort i.e. as the compactive effort is increased the effect of moisture content increases.

Table 4 shows that as the moisture content increases the effect of rate of strain on increasing the strength increases for a given compactive effort. However, it should be noted that this relationship is generally valid for only the dry side of optimum since the data on the wet side are incomplete.

Table 4 also shows that some clay soils may decrease in strength with an increase in rate of strain. This tendency existed at all except one moisture content, the highest, at the lowest compactive effort. In the two higher compactive efforts the condition existed at only one moisture content, in each. Since the latter values are so close to unity, it could be assumed that there was not a decrease and the stress ratio is unity.

However, due to the fact that the stress ratios for the medium transient tests are consistently less than 1.0 this might be a significant trend, for the lowest compactive effort. It can also be noted that a value of the stress ratio greater than 1.0 occurs at nearly the optimum moisture content. This indicates that on the wet side, stress ratios greater than 1.0 would be obtained. Also, it must be recognized

Clay

For the clay, it was also found that for a given compactive effort and moisture content, increasing the rate of strain produced a measurable increase in the strength of the soil (Figure 6). As with the silty clay, the strength ratio, for all moisture contents, was greatest for the lowest compactive effort (Table 4). Also, from Figure 6 it can be seen that moisture content has less effect on the strength, at a given rate of strain, the lower the compactive effort i.e. as the compactive effort is increased the effect of moisture content increases.

Table 4 shows that as the moisture content increases the effect of rate of strain on increasing the strength increases for a given compactive effort. However, it should be noted that this relationship is generally valid for only the dry side of optimum since the data on the wet side are incomplete.

Table 4 also shows that some clay soils may decrease in strength with an increase in rate of strain. This tendency existed at all except one moisture content, the highest, at the lowest compactive effort. In the two higher compactive efforts the condition existed at only one moisture content, in each. Since the latter values are so close to unity, it could be assumed that there was not a decrease and the stress ratio is unity.

However, due to the fact that the stress ratios for the medium transient tests are consistently less than 1.0 this might be a significant trend, for the lowest compactive effort. It can also be noted that a value of the stress ratio greater than 1.0 occurs at nearly the optimum moisture content. This indicates that on the wet side, stress ratios greater than 1.0 would be obtained. Also, it must be recognized

FIG. 6. RATE OF STRAIN VS UNCONFINED COMPRESSIVE STRENGTH — CLAY

TABLE 1.

SUMMARY OF RESULTS OF STRENGTH TESTS - CLAY

RATE STRAIN	COMPACTIVE EFFORT					
	3 Layers/25 Blows		10 Layers/25 Blows		10 Layers/50 Blows	
	MOISTURE CONTENT = 18%					
	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio
0.55 "/min.	56	1.00	94	1.00	131	1.00
13.5 "/min.	44	0.79	98	1.04	126	0.96
1140 "/min.	97	1.73	142	1.51	160	1.22
	MOISTURE CONTENT = 20%					
	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio
0.55 "/min.	61	1.00	103	1.00	115	1.00
13.5 "/min.	49	0.80	100	0.97	136	1.18
1140 "/min.	104	1.71	146	1.42	160	1.39
	MOISTURE CONTENT = 22%					
	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio
0.55 "/min.	58	1.00	89	1.00	93	1.00
13.5 "/min.	50	0.86	93	1.04	128	1.36
1140 "/min.	102	1.76	137	1.54	146	1.57
	MOISTURE CONTENT = 24%					
	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio
0.55 "/min.	49	1.00	71	1.00	69	1.00
13.5 "/min.	48	0.98	80	1.13	98	1.42
1140 "/min.	92	1.88	117	1.65	120	1.74
	MOISTURE CONTENT = 26%					
	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio	Strength (psi.)	S _u Ratio
0.55 "/min.	38	1.00	48	1.00	45	1.00
13.5 "/min.	43	1.13	63	1.31	70	1.56
1140 "/min.	80	2.11	91	1.90	95	2.11

that since the stress ratio for the medium transient tests are generally very close to unity, at low moisture contents and low compressive efforts, and since an average curve is drawn through the data obtained this would account for the stress ratio being less than 1.0.

A study of Figure 6 reveals that the higher the compressive effort the greater the effect of a change in moisture content on the strength of the clay soil. For example, as the compressive effort is increased the curves in Figure 6 become farther apart.

It should be noted that the 18 per cent moisture content curve in Figure 6 is out of line with the remainder of the data. This is probably because of specimens tested at this moisture content failed, partially at least, by crumbling.

Figure 7 illustrates, qualitatively, that the effect of an increase in density, decreases as the rate of strain increases. This can be noted from the fact that the slopes of the curves for rate of strain equal to 1140 inches per minute are less than those for either 0.55 or 13.5 inches per minute.

It is worthy of note that the strength ratio for the clay increases with increasing moisture content while that for the silty clay decreases with increasing moisture content. Also, for a given rate of strain the effect of moisture content on the strength is greater for the silty clay than the clay. However, the latter trend decreases as the compressive effort decreases.

Modulus of Deformation

The data on the modulus of deformation, for both soils tested, was the most difficult to interpret. This was due to the large scattering of the values (see Figures 2 and 3). The latter situation being caused by the difficulty in picking values from the oscilloscope trace. It was quite easy to determine the maximum load, on the specimen, and the

FIG. 7 DRY DENSITY VS. UNCONFINED COMPRESSIVE STRENGTH - CLAY

strain at which it occurred. However, at low loads it was, in many instances, impossible to accurately determine the load on the specimen and the strain at which it occurred. As a result, in practically all cases, the initial portions of all stress strain curves appeared to be out of line.

Consequently, the modulus of deformation vs. moisture content curves, for a given compactive effort and rate of strain can only be used to obtain general trends as indicated by the results shown (Figures 2 and 3). Since the modulus of deformation vs. rate of strain curves (Figures 8 and 9), for a given moisture content and compactive effort, were obtained from the curves previously indicated they, also, are only of qualitative value.

Silty Clay

Regardless of the scattering of the points in Figure 2 it can be readily seen that moisture content has a tremendous effect on the modulus of deformation of the silty clay. It is also apparent that as the rate of strain increases the effect of moisture on the modulus of deformation also increases.

This rate of change of modulus of deformation with respect to a change in moisture content decreases as the moisture content increases until a point is reached where the compactive effort has a negligible effect on the modulus of deformation. This condition occurs on the dry side of optimum for the slow and medium transient tests, for all compactive efforts, and approximately at optimum for the fast transient tests.

In fact, if a soil is to be compacted at a moisture content which approximates the O.M.C. for standard compaction, considering the fast transient test conditions, it appears that use of a compactive effort greater than Standard Proctor is not warranted. Considering the fact

that a subgrade usually gains approximately 2 per cent moisture before coming to equilibrium with its natural surroundings, this would make compaction at an effort greater than standard AASHTO impractical, unless methods of preventing an increase in moisture content were provided. The latter statement is assuming that the modulus of deformation is to be used as the criterion of strength.

Considering the moisture content range tested it appears a significant increase in modulus of deformation due to an increase in rate of strain was obtained only for the specimens compacted at about 10 per cent moisture (Figure 8). This is true regardless of the compactive effort. Also, on the basis of Figure 8 it can be easily seen that moisture content has a much more significant effect on the modulus of deformation than does rate of strain.

As regards moisture contents of 12 per cent or above it appears that an increase in the rate of strain will not produce an increase in the modulus of deformation. From Figure 8 and Table 5 it can be seen that for certain moisture contents there appears to be a decrease in the modulus of deformation with an increase in the rate of strain. This can probably be attributed to the scattering of data. Also, the scattering of data might be the reason there was a significant increase in modulus of deformation with rate of strain for the 10 per cent moisture content specimens.

Table 5 indicates an important trend. For a given compactive effort and rate of strain the H_D ratio decreases with increasing moisture content. There was, however, too much variability of data to make quantitative comparisons between various compactive efforts.

Clay

In the clay soil there was also a substantial decrease in the modulus of deformation for a given increase in moisture content at a

FIG. 8. RATE OF STRAIN VS. MODULUS OF DEFORMATION — SILTY CLAY

TABLE 5

SUMMARY OF MODULUS OF DEFORMATION DATA - SILTY CLAY

RATE STRAIN	COMPACTIVE EFFORT					
	3 Layers/25 Blows		10 Layers/25 Blows		10 Layers/50 Blows	
0.55 "/min. 14.5 "/min. 1768 "/min.	MOISTURE CONTENT = 10%					
	M _D (psi.)	M _D Ratio	M _D (psi.)	M _D Ratio	M _D (psi.)	M _D Ratio
	2700	1.00	6700	1.00	3700	1.00
	3900	1.46	11,300	1.69	7400	1.30
	6200	2.30	20,000	3.22	20,600	3.61
0.55 "/min. 14.5 "/min. 1768 "/min.	MOISTURE CONTENT = 12%					
	M _D (psi.)	M _D Ratio	M _D (psi.)	M _D Ratio	M _D (psi.)	M _D Ratio
	2900	1.00	4200	1.00	5200	1.00
	2950	1.02	3600	0.86	3400	0.65
	2400	0.83	5600	1.33	5200	1.00
0.55 "/min. 14.5 "/min. 1768 "/min.	MOISTURE CONTENT = 14%					
	M _D (psi.)	M _D Ratio	M _D (psi.)	M _D Ratio	M _D (psi.)	M _D Ratio
	2200	1.00	2050	1.00	2500	1.00
	1950	0.88	1600	0.78	1400	0.56
	550	0.25	2250	1.10	1250	0.50
0.55 "/min. 14.5 "/min. 1768 "/min.	MOISTURE CONTENT = 16%					
	M _D (psi.)	M _D Ratio	M _D (psi.)	M _D Ratio	M _D (psi.)	M _D Ratio
	1040	1.00	600	1.00	150	1.00
	1000	0.96	600	1.00	500	3.33
	250	0.24	550	0.92	150	1.00
0.55 "/min. 14.5 "/min. 1768 "/min.	MOISTURE CONTENT = 17%					
	M _D (psi.)	M _D Ratio	M _D (psi.)	M _D Ratio	M _D (psi.)	M _D Ratio
	800	1.00	200	1.00	75	1.00
	450	0.56	350	1.75	200	2.67
	200	0.25	200	1.00	50	0.67

given rate of strain (Figure 9). This condition was more pronounced the higher the compactive effort and the greater the rate of strain. On the basis of the data given, at moisture contents approximating the optimum moisture content for Standard AASHO the effect on the modulus of deformation of an increase in compactive effort is negligible. However, as the rate of strain increases the effect of the amount of compactive effort becomes apparent.

From Figure 9 and Table 6 the effect of rate of strain and moisture content on the modulus of deformation can be observed. For all compactive efforts and rates of strain there was a tendency toward an increase in modulus of deformation with an increase in rate of strain. In a few instances, particularly the medium transient tests at the intermediate compactive effort, there was a slight decrease in the modulus of deformation with an increase in rate of strain. This can be attributed to the scattering of the data, and the attempt to draw a representative curve through it. The aforementioned reason was also the cause of the M_D ratios being less than one, in all probability (Table 6).

Consequently, it can be stated that for a given rate of strain the M_D ratio increases with increasing moisture content. Also, the M_D ratio, for a given moisture content and the fast transient test conditions, increased as the compactive effort increased. This tendency was not apparent in the M_D ratio for the medium transient tests.

In the case of the intermediate effort, considering the medium transient tests, the value of the M_D ratio obtained was much less than either of the other two compactive efforts. Also, the caliber of the data did not produce results from which a general trend could be pre-

FIG. 9. RATE OF STRAIN VS. MODULUS OF DEFORMATION — CLAY

TABLE 6

SUMMARY OF MODULUS OF DEFORMATION DATA - CLAY

RATE STRAIN	COMPACTIVE EFFORT					
	3 Layers/25 Blows		10 Layers/25 Blows		10 Layers/50 Blows	
	MOISTURE CONTENT = 18%					
	M_D (psi.)	M_D Ratio	M_D (psi.)	M_D Ratio	M_D (psi.)	M_D Ratio
0.55 "/min.	4300	1.00	8300	1.00	10,900	1.00
13.5 "/min.	5100	1.19	6000	0.72	13,400	1.23
1140 "/min.	4400	1.02	13,900	1.66	18,700	1.71
	MOISTURE CONTENT = 20%					
	M_D (psi.)	M_D Ratio	M_D (psi.)	M_D Ratio	M_D (psi.)	M_D Ratio
0.55 "/min.	2800	1.00	5300	1.00	7000	1.00
13.5 "/min.	4600	1.64	4400	0.70	8900	1.27
1140 "/min.	3800	1.36	10,700	1.70	15,000	2.14
	MOISTURE CONTENT = 22%					
	M_D (psi.)	M_D Ratio	M_D (psi.)	M_D Ratio	M_D (psi.)	M_D Ratio
0.55 "/min.	2200	1.00	4500	1.00	4200	1.00
13.5 "/min.	4000	1.80	3100	0.69	6200	1.48
1140 "/min.	3200	1.45	8000	1.78	11,600	2.76
	MOISTURE CONTENT = 24%					
	M_D (psi.)	M_D Ratio	M_D (psi.)	M_D Ratio	M_D (psi.)	M_D Ratio
0.55 "/min.	1700	1.00	3000	1.00	2300	1.00
13.5 "/min.	3400	2.00	2200	0.73	4100	1.78
1140 "/min.	2600	1.53	5600	1.87	8300	3.61
	MOISTURE CONTENT = 26%					
	M_D (psi.)	M_D Ratio	M_D (psi.)	M_D Ratio	M_D (psi.)	M_D Ratio
0.55 "/min.	1500	1.00	1600	1.00	1200	1.00
13.5 "/min.	2800	1.87	2000	1.25	2600	2.17
1140 "/min.	1900	1.27	3600	2.25	5300	4.41

dicted for the medium transient tests i.e. no definable tendency of the variance of the M_D ratio of the medium transient tests at a given moisture content but varying compactive effort.

As can be seen from Figure 9 moisture content has an increasingly important effect on the modulus of deformation the higher the compactive effort. Also, it is shown that significant increases in the modulus of deformation may be obtained by increasing the rate of strain. It should be noted that the higher the compactive effort the greater the effect of rate of strain on M_D .

For the lowest compactive effort, a decrease in M_D for an increase in rate of strain was noted (Figure 9). This is probably due to the scattering of data and the use of average curves.

Comparison of Clay and Silty Clay

In both the clay and silty clay, a significant increase in unconfined compressive strength occurred with an increase in rate of strain for all compactive efforts and all moisture contents tested. However, with the silty clay, as the moisture content increased, the strength ratio decreased while for the clay the converse was true.

In both the clay and the silty clay the strength ratios for the fast transient test were greater for the lowest compactive effort. No definite relationship could be established for the medium transient tests between the strength ratios and the compactive effort.

In both the clay and the silty clay the moisture content proved to be more significant than the increase in rate of strain, as regards affecting the unconfined compressive strength. This tendency became less as the compactive effort decreased.

Moisture content has a great effect on the modulus of deformation of the silty clay as well as the clay. This condition was more pronounced the higher the compactive effort and the higher the rate of

strain. Furthermore, for the clay soil, increasing the rate of strain produced a measurable increase in the M_p ratio, but this was not the case for the silty clay.

It is worthy to note that the data presented in this report do not give a straight line relationship, on a semi-logarithmic plot, for the variance of strength or modulus of deformation with respect to rate of strain (Figures 4, 6, 8 and 9). The aforementioned is not surprising due to large number of variables present. Nevertheless, such a relationship can be obtained for certain soils, as is shown in reference 23.

From Tables 3 and 4 it can be readily seen why the effect of rate of strain is more significant in increasing the strength of the material at low density. This fact may be ascertained by comparing the difference in strength between the fast and slow transient tests for the same moisture content but varying densities. It can be seen that the increase in strength is relatively constant regardless of the compactive effort. Thus, due to the much lower slow transient strength of the material at low density, it is to be expected to show a greater percentage increase in strength for a given increase in rate of strain.

Also, it is interesting to note that the aforementioned difference is less variable, with moisture content, for the clay than the silty clay. This is because the silty clay is much more susceptible to changes in moisture content.

In contrast to Whitman (23), the data show a general trend toward a decrease in the strain at failure with an increase in the rate of strain. This is attributed to the fact that the faster the rate of strain the faster the load is applied which results in the specimen not having the opportunity of deforming greatly before it develops its maximum shear strength.

Finally, it is of interest to investigate the possibility of thixotropic action affecting the results, since the specimens were tested approximately 24 hours after molding. Both Moretto (24) and Skempton and Northey (25) observed that thixotropic strength regain decreased with decreasing water content below the liquid limit. Also, Seed and Chan (26) showed that thixotropic effects are relatively small, for samples compacted on the dry side of optimum for the compactive effort being used.

It is realized that the thixotropic effect is not a well known phenomenon. Consequently, the results published by one investigator may be used by another only if the material and the test procedures are quite similar. Nevertheless, it was felt that the aforementioned work could be used as a guide to the design of the experiment. Thus, by testing specimens at moisture contents well below the liquid limit and by limiting the time of storage to a maximum of twenty-four hours, it was hoped that the effects of thixotropy would be relatively constant for all tests.

CONCLUSIONS

On the basis of these tests, and for the soils involved, it can be concluded that:

1. As the compactive effort is increased the greater the effect of changes in moisture content on the unconfined compressive strength, regardless of the rate of strain.
2. The lower the compactive effort the greater the effect of rate of strain on the strength.
 - a. Considering the silty clay, as the moisture content increases the strength ratio tends to decrease.
 - b. Considering the clay, as the moisture content increases the strength ratio increases.
3. As the rate of strain increases the effect of an increase in dry density, at a given moisture content, on the unconfined compressive strength decreases.
4. Increasing the rate of strain produced a measurable increase in the M_D ratio of the clay soil.
 - a. For the clay soil, as the moisture content increased the M_D ratio increased for a given compactive effort but the highest compactive effort yielded the greatest increase.
 - b. In the silty clay soil there was a tendency toward a decrease in M_D ratio for a given rate of strain and compactive effort.
 - c. Due to the scattering of data it was impossible to compare the M_D ratios of the various compactive efforts and establish a trend.
5. On the basis of these tests it must be concluded that to obtain significant increases in strength or modulus of deformation it takes a rate of strain equivalent to a fast transient test.

6. As the rate of strain decreases there is a tendency for the strain at failure to increase.

BIBLIOGRAPHY

1. Casagrande, A. and Shannon, W. L., Research on Stress - Deformation and Strength Characteristics of Soils and Soft Rocks Under Transient Loading, Soil Mechanics, Series No. 31, No. 117, Harvard University, 1948.
2. Abrams, D. A., "Effect of Rate of Loading on the Compressive Strength of Concrete", Proceedings, American Society for Testing Materials, Vol. 17, Part II, 1917, p. 366-378.
3. Evans, R. H., "Effect of Rate of Loading on the Mechanical Properties of Some Materials", Journal of the Institution of Civil Engineers, Vol. 18, 1912, p. 296-306.
4. Jones, P. G. and Richart, F. E., "The Effect of Testing Speed on Strength and Plastic Properties of Concrete", Proceedings, American Society for Testing Materials, Vol. 16, Part 2, 1936, p. 380-392.
5. Thompson, J. T., "Static and Impact Strains in Concrete", Public Roads, Vol. 7, No. 5, July, 1926, p. 91-100.
6. Manjoine, M. J. and Kadai, "High Speed Tension Tests at Elevated Temperatures", Proceedings, American Society for Testing Materials, Vol. 40, 1940, p. 822-828.
7. Ide, J. M., "Some Dynamic Methods for Determination of Young's Modulus", The Review of Scientific Instruments, Vol. 6, 1935, p. 296-298.
8. Sears, J. E., "Longitudinal Impact of Bars with Rounded Ends", Transactions, Cambridge Philosophical Society, Vol. 21, No. 2, 1908, p. 49-105.
9. King, A., "A New Method for Measuring Young's Modulus", Review of Scientific Instruments, Vol. 11, 1940, p. 114-116.
10. King, A., "Ring Method for Measuring Elastic Moduli", Review of Scientific Instruments, Vol. 14, 1943, p. 31-34.
11. Brokaw, H. P. and Foster, G. W., Effect of Rapid Loading and Duration of Stress on the Strength Properties of Wood Tested in Compression and Flexure, U. S. Department of Agriculture, Forest Products Laboratory, Madison, Wisconsin, January, 1945.
12. Ide, J. M., "Comparison of Statically and Dynamically Determined Young's Modulus of Rocks", Proceedings, National Academy of Sciences, Vol. 22, No. 2, February 1936, p. 81-92.
13. Evans, R. H., "Instantaneous Strains in Building Materials", Proceedings, Leeds Philosophical and Literary Society, Vol. 3, Part II, July, 1940, p. 581.

14. New Datum Loose Black Muck Slope Design, Special Engineering Division, The Panama Canal, October 1942.
15. Seed, H. B. and Lundgren, R., Investigation of the Effect of Transient Loading on the Strength and Deformation Characteristics of Saturated Sands, Institute of Transportation and Traffic Engineering, University of California, reprint No. 32.
16. Lovell, C. W. Jr., Certain Characteristics of Partially-Frozen Soils, Doctor's Thesis, Graduate School of Engineering, Purdue University, August 1956.
17. Belcher, D. J. et. al., The Formation Distribution and Engineering Characteristics of Soils, Research Series No. 87, Highway Research Bulletin No. 10, Purdue University, Lafayette, Indiana, January 1943, p. 116-304.
18. Lambe, T. W., Soil Testing for Engineers, Wiley, New York, 1951.
19. Corps of Engineers, The Unified Soil Classification System, Technical Memorandum No. 3-357, Vol. 1, Waterways Experiment Station, Vicksburg, Miss., March 1953, 30 pp.
20. DuMont Laboratories, DuMont Oscillograph Record Camera Type 292. Operating and Maintenance Manual, Allen B. DuMont Laboratories, Clifton, N. J.
21. DuMont Laboratories, Techniques of Photo-Recording from Cathode-ray Tubes, 3rd Edition, Allen B. DuMont Laboratories, Clifton, N. J.
22. Wilson, S. D., "Small Soil Compaction Apparatus Duplicates Field Results Closely", Engineering News Record, Vol. 115, No. 18, November 2, 1950, p. 34-36.
23. Whitman, R. V., "The Behavior of Soils Under Transient Loadings", Proceedings of the Fourth International Conference on Soil Mechanics and Foundation Engineering, London, 1957.
24. Hampton, Delon, Effect of Rate of Strain on the Strength of Remolded Soil, Master's Thesis, Graduate School of Engineering, Purdue University, June 1958.